

Index


- Properties 5cm angled antenna page 2
- Properties 5cm straight antenna page 3
- Properties 15cm antenna page 4
- Properties 36cm antenna page 5
- Testing result (received from manufacturer) page 6
- Ordering Information page 16

For more information visit:

<http://www.in-circuit.de/>

<http://www.radino.cc/>

Properties 5cm angled antenna




Frequency	433 MHz	868 MHz	2.4 GHz
Input Impedance	50 Ω		
V.S.W.R	≤ 1.5		
Polarization Intensity	R.H.C.P		
Supply Voltage	DC 3.0 ~ 5.0 V		
Sound Coefficient	≤ 1.5 dB		
Gain	3 dBi		
Radiator	Cuprum		
Connector Type	RPSMA male (have no pin inside)		
Color	black		
Operating Temperatur	$-40^{\circ}\text{C} \sim + 85^{\circ}\text{C}$		
Storing Temperatur	$-40^{\circ}\text{C} \sim + 90^{\circ}\text{C}$		
Radome material	TPU		
Dimension	45 mm		

Properties 5cm straight antenna




Frequency	433 MHz	868 MHz	2.4 GHz
Input Impedance	50 Ω		
V.S.W.R	≤ 1.5		
Polarization Intensity	Vertical		
Supply Voltage	DC 3.0 ~ 5.0 V		
Sound Coefficient	≤ 1.5 dB		
Gain	3 dBi		
Radiator	Cuprum		
Connector Type	RPSMA male (have no pin inside)		
Color	black		
Operating Temperatur	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$		
Storing Temperatur	$-40^{\circ}\text{C} \sim +90^{\circ}\text{C}$		
Radome material	TPE		
Dimension	48 mm		

Properties 15cm antenna



Frequency	433 MHz	868 MHz
Input Impedance	50 Ω	
V.S.W.R	≤ 1.5	
Polarization Type	Vertical	
Radiation	Omni directional	
Supply Voltage	DC 3.0 ~ 5.0 V	
Max Input Power	50 W	
Gain	5 dBi	
Radiator	Cuprum	
Connector Type	RPSMA male (have no pin inside)	
Operating Temperatur	-40°C ~ + 85°C	
Storing Temperatur	-40°C ~ + 90°C	
Antenna length	198 mm	




Properties 36cm antenna



Frequency	433 MHz	868 MHz
Input Impedance	50 Ω	
V.S.W.R	≤ 1.5	
Polarization Intensity	R.H.C.P	
Supply Voltage	DC 3.0 ~ 5.0 V	
Sound Coefficient	≤ 1.5 dB	
Gain	8 dBi	
Radiator	Cuprum	
Connector Type	RPSMA male (have no pin inside)	
Color	black	
Operating Temperatur	-40°C ~ + 85°C	
Storing Temperatur	-40°C ~ + 90°C	
Radome material	ABS	
Dimension	375 mm	




Testing result 5cm angled 433 MHz

Received from manufacturer




Testing result 5cm angled 868 MHz

Received from manufacturer




Testing result 5cm angled 2.4 GHz


Received from manufacturer



H-PLANE




E-PLANE




Testing result 5cm straight 433 MHz


Received from manufacturer



H-PLANE






E-PLANE



Testing result 5cm straight 868 MHz

Received from manufacturer




Testing result 5cm straight 2.4 GHz


Received from manufacturer



H-PLANE




E-PLANE




Testing result 15cm 433 MHz

Received from manufacturer




Testing result 15cm 868 MHz


Received from manufacturer



H-PLANE




E-PLANE




Testing result 36cm 433 MHz

Received from manufacturer





Testing result 36cm 868 MHz

Received from manufacturer



H-PLANE

E-PLANE



Ordering Information

Part	Ordering Code	MOQ	Package
5cm angled 433 MHz	303.292	1	Single device in anti-static bubble bag
5cm angled 868 MHz	303.281	1	Single device in anti-static bubble bag
5cm angled 2.4 GHz	303.294	1	Single device in anti-static bubble bag
5cm straight 433 MHz	303.291	1	Single device in anti-static bubble bag
5cm straight 868 MHz	303.290	1	Single device in anti-static bubble bag
5cm straight 2.4 GHz	303.293	1	Single device in anti-static bubble bag
15cm 433 MHz	303.283	1	Single device in anti-static bubble bag
15cm 868 MHz	303.282	1	Single device in anti-static bubble bag
36cm 433 MHz	303.327	1	Single device in anti-static bubble bag
36cm 868 MHz	303.285	1	Single device in anti-static bubble bag

Revision history:

Version	Date	Changes	Editor
A	2017/06/09	Initial Version	Grünig